

Civacon Plug & Cord Set from OPW-ES

The Civacon Plug & Cord Set has been designed to prevent equipment damage while saving operators the time and money that can be lost as a result of unplugged driveaways. The Breakaway Plug & Cord Set utilizes high-quality, corrosion-resistant materials for reliable long-life operation.



Junction Box 7540-7540



Plug & Cord 7120-7120



Junction Box 7510T-7510



Plug & Cord 7320-7320

FEATURES & BENEFITS

- Lightweight molded plug for ease of installation/use/handling
- Stainless-steel contact pins for enhanced corrosion-resistance
- Heavy-gauge spring behind contact pins ensures strong, reliable electrical connections
- 18-gauge tinned wire fights corrosion
- 30-foot coiled-cord length for high-visibility, ease of use and safety
- Color-coded wiring for ease of identification/ installation
- Stainless-steel interlock screws with 3/4 opening for easy replacement of the plug cord

SPECIFICATIONS

Operating Temperature: -40°F to 158°F (-40°C to 70°C)
Materials: Plug Body - Urethane Rubber Contact Pins - Stainless Steel
Type: SJO
Jacket: Viscosity Fuel Resistant
Length Retracted: 5'
Length Extended: 30'
Wire Size: 18 gauge

PRODUCT	PRODUCT #	DESCRIPTION
PLUG & CORD (select thermistor or optic)	7100-7100	Optic Plug with 30' 10-conductor coiled cord
	7120-7120	Optic Plug with 30' 10-conductor coiled cord and 7-pin breakaway plug
	7100SR-7100	Optic Plug with 30' 6-conductor blue coiled cord for Scully replacement
	7120SR-7120	Optic Plug with 30' 6-conductor blue coiled cord for Scully replacement and 7-pin breakaway plug
	7300-7300	Thermistor Plug with 30' 10-conductor coiled cord
	7300C-7300	Thermistor Plug with 30' 10-conductor coiled cord (Canada only)
	7320-7320	Thermistor Plug with 30' 10-conductor coiled cord and 13-pin breakaway plug
	7300SR-7300	Thermistor Plug with 30' 10-conductor coiled cord for Scully replacement
	7320SR-7320	Thermistor Plug with 30' 10-conductor coiled cord for Scully replacement and 13-pin breakaway plug
JUNCTION BOX	7500-7500	Junction Box for Optic, Thermistor and Ground Verification Plug and Cord Sets (Non-Breakaway)
	7540-7540	Junction Box with 7-pin socket for Cane Probes or Breakaway Optic Plug & Cord Set
	7510T-7510	Junction Box with 13-pin socket for breakaway Thermistor Plug & Cord Set

